

TECHNICAL STANDARDS FOR HARVEY MARIA VINYL TILE

Collections: Authentic Stone, Natural Oak, Rustic Wood

| Standard | Construction Specifications |
|---|---|
| Floorcovering to ISO 10581 ISO 14001 ISO 9001 | Heterogeneous PVC ✓ ✓ |
| ISO 24340 Thickness of wear layer ISO 24346 Total thickness | 0.55mm + Polyurethane 2.5mm |
| ISO 23997 Weight | +/- 4.350 kgs/m ² |
| EN 1081 Electrical resistance | Horizontal: >1.0 x 10 ¹⁶ Ω Vertical: 1.0 x 10 ¹³ Ω |
| EN 1815 Anti-static performance | Rubber sole: +6.6kV PVC sole: +4.0kV |
| ISO 10140-1 Maximum acoustic insulation | ΔLw 2dB |
| ISO 354 Maximum sound absorption | αw 0.05 |
| EN 12667 / ISO 8302 Thermal resistance EN 13501-1:2007 Burning behaviour | 0.005m ² K/W Bfl-s1 |
| ISO 24343-1 Point load resistance | 0.51mm |
| ISO 4918 Castor chair resistance | ✓ |
| EN 13893 Slip resistance | 0.7mμ (R9) |
| ISO 10582 Usage category | 33 - Heavy commercial use 42 - Light industrial use |
| ISO 26987 Resistance to chemicals | Class O - Good |
| ISO 24344A Flexibility | 20mm |
| EN 71 Toxicity | Non toxic |
| AgBB/DIBt low VOC | Certified ✓ |
| EN ISO 105-B02 Light fastness | 6- 8 Dependent on design |
| Underfloor heating | 28 °C ✓ |

